



DATA SHEET 12006.750.11300

## Folabase Soft A

The Folabase Soft A is the self-adhesive modulation of our modern and flexible Folabase Soft u. The two-layer compound made of dimensionally stable polyester and extremly ductile polyurethane ensures an extremely high dimensional stability and thus, stable thickness. The soft polyrethane layer absorbs mechanical forces and ensures a good resistance against paper jam.

For product introduction by video please click here.

Formats		
Art.Number	Nominal thickness (inch)	Nominal thickness (mm)
12006.350.99900	.0138	0.35
12006.400.99900	.0157	0.40
12006.450.99900	.0177	0.45
12006.500.99900	.0197	0.50
12006.550.99900	.0217	0.55
12006.600.99900	.024	0.60
12006.700.99900	.028	0.70
12006.750.99900	.0295	0.75
12006.800.99900	.0315	0.80
12006.900.99900	.035	0.90
12006.950.99900	.037	0.95
12006.110.99900	.043	1.10
12006.130.99900	.051	1.30
12006.140.99900	.055	1.40

#### Art.Number Nominal thickness Nominal thickness Roll width / Roll Length of roll (inch) (mm) usuable width 12006.550.99900 .0217 0.55 12006.350.11300 .0138 0.35 1270 50 12006.400.11300 0.40 1270 50 .0157

Rolls



12006.450.11300	.0177	0.45	1270	50	
12006.500.11300	.0197	0.50	1270	50	
12006.550.11300	.0217	0.55	1270	50	
12006.600.11300	.024	0.60	1270	50	
12006.700.11300	.028	0.70	1270	50	
12006.750.11300	.0295	0.75	1270	50	
12006.800.11300	.0315	0.80	1270	50	
12006.900.11300	.035	0.90	1270	50	
12006.950.11300	.037	0.95	1270	50	
12006.110.11300	.043	1.10	1270	50	
12006.130.11300	.051	1.30	1270	50	
12006.140.11300	.055	1.40	1270	50	

## Technical data

### Characteristic







- Paper jam-resistant Crease-resistant / self-healing
- Polyester-basis/ -carrier
- Adhesive light

#### **Finish**

• Soft surface

# Compatibility

- For Blanket Cylinder
- For a hard substrate packing.
- Paperlike underpacking film

### Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.



