

DATA SHEET 12001.350.99900

Folabase Soft U

UNDERPACKING FOIL, NON ADHESIVE

Folabase Soft U offers reliable support for adaptation to cylinder circumferences and print lengths in offset printing presses and ensures optimum dot transfer.

The two-layer compound made of dimensionally stable polyester and extremely ductile polyurethane ensures an extremely high dimensional stability and consistent thickness.

Unlike paper-based underpacking sheets the Folabase Soft U has a certain smash resistance and can be used again. Additionally it is highly swell resistant to dampening solutions and cleaning agents.

For product introduction by video please click [here](#).

Formats

| Art.Number | Nominal thickness (inch) | Nominal thickness (mm) |
|-----------------|--------------------------|------------------------|
| 12001.350.99900 | .014 | 0.35 |
| 12001.400.99900 | .016 | 0.40 |
| 12001.450.99900 | .018 | 0.45 |
| 12001.500.99900 | .020 | 0.50 |
| 12001.550.99900 | .022 | 0.55 |
| 12001.600.99900 | .024 | 0.60 |
| 12001.700.99900 | .028 | 0.70 |
| 12001.750.99900 | .030 | 0.75 |
| 12001.800.99900 | .031 | 0.80 |
| 12001.900.99900 | .035 | 0.90 |
| 12001.950.99900 | .037 | 0.95 |
| 12001.105.99900 | .041 | 1.05 |
| 12001.110.99900 | .043 | 1.10 |
| 12001.130.99900 | .051 | 1.30 |
| 12001.145.99900 | .057 | 1.45 |

Rolls

| Art.Number | Width (mm) | Length (m) | Nominal thickness (inch) | Nominal thickness (mm) |
|-----------------|------------|------------|-----------------------------|---------------------------|
| 12000.350.11300 | 1270 | 50 | .014 | 0.35 |
| 12001.400.11300 | 1270 | 50 | .016 | 0.40 |
| 12001.450.11300 | 1270 | | .018 | 0.45 |
| 12001.500.11300 | 1270 | | .020 | 0.50 |
| 12001.550.11300 | 1270 | | .022 | 0.55 |
| 12001.600.11300 | 1270 | | .024 | 0.60 |
| 12001.700.11300 | 1270 | | .028 | 0.70 |
| 12001.750.11300 | 1270 | | .030 | 0.75 |
| 12001.800.11300 | 1270 | | .031 | 0.80 |
| 12001.900.11300 | 1270 | | .035 | 0.90 |
| 12001.950.11300 | 1270 | | .037 | 0.95 |
| 12001.105.11300 | 1270 | 50 | .041 | 1.05 |
| 12001.110.11300 | 1270 | 50 | .043 | 1.10 |
| 12001.130.11300 | 1270 | 50 | .051 | 1.30 |
| 12001.145.11300 | 1270 | 50 | .057 | 1.45 |

Technical data

Characteristic



- Paper jam-resistant Crease-resistant / self-healing
- Polyester-basis/ -carrier

Finish

- Soft surface

Compatibility

- Paperlike underpacking film

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the

complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.



FOLABASE SOFT U

weiche, dämpfende PU Schicht



Polyesterfolie
(Trägermaterial)