

DATA SHEET 12015.100.99900

Folabase H 48

UNDERPACKING FOIL, SELF-ADHESIVE

Folabase H48 is a new Folex product in the segment of self-adhesive underpacking foils. Corrosion-inhibiting additives in our Folabase H48 underpacking foil protect the cylinder surface. The foil can be easily applied to almost all cylinders and can be removed quickly and cleanly with very little cleaning effort. The foil's release film consists of siliconised propylene, this prevents wrinkling and avoids dust inclusion. Given its high resistance to chemical cleaners and solvents, Folabase H48 is characterised by a long service life. The foil demonstrates very good thermal stability on the press.

For product introduction by video please click [here](#).

Formats

| Art.Number | Nominal thickness (inch) | Nominal thickness (mm) |
|-----------------|--------------------------|------------------------|
| 12015.080.99900 | .0031 | 0.08 |
| 12015.100.99900 | .0039 | 0.10 |
| 12015.120.99900 | .0047 | 0.12 |
| 12015.140.99900 | .0055 | 0.14 |
| 12015.160.99900 | .0063 | 0.16 |
| 12015.180.99900 | .0071 | 0.18 |
| 12015.200.99900 | .0079 | 0.20 |
| 12015.220.99900 | .0087 | 0.22 |
| 12015.240.99900 | .0094 | 0.24 |
| 12015.260.99900 | .0102 | 0.26 |
| 12015.280.99900 | .0110 | 0.28 |
| 12015.300.99900 | .0118 | 0.30 |
| 12015.320.99900 | .0126 | 0.32 |
| 12015.350.99900 | .0138 | 0.35 |
| 12015.400.99900 | .0157 | 0.40 |
| 12015.450.99900 | .0177 | 0.45 |
| 12015.500.99900 | .0217 | 0.50 |

Rolls

| Art.Number | Width (mm) | Length (m) | Nominal thickness (inch) | Nominal thickness (mm) |
|-----------------|------------|------------|-----------------------------|---------------------------|
| 12015.080.31350 | 1270 | 50 | .0031 | 0.08 |
| 12015.100.31350 | 1270 | 50 | .0039 | 0.10 |
| 12015.120.31350 | 1270 | 50 | .0047 | 0.12 |
| 12015.140.31350 | 1270 | 50 | .0055 | 0.14 |
| 12015.160.31350 | 1270 | 50 | .0063 | 0.16 |
| 12015.180.31350 | 1270 | 50 | .0071 | 0.18 |
| 12015.200.31350 | 1270 | 50 | .0079 | 0.20 |
| 12015.220.31350 | 1270 | 50 | .0087 | 0.22 |
| 12015.240.31350 | 1270 | 50 | .0094 | 0.24 |
| 12015.260.31350 | 1270 | 50 | .0102 | 0.26 |
| 12015.280.31350 | 1270 | 50 | .0110 | 0.28 |
| 12015.300.31350 | 1270 | 50 | .0118 | 0.30 |
| 12015.320.31350 | 1270 | 50 | .0126 | 0.32 |
| 12015.350.31350 | 1270 | 50 | .0138 | 0.35 |
| 12015.400.31350 | 1270 | 50 | .0157 | 0.40 |
| 12015.450.31350 | 1270 | 50 | .0177 | 0.45 |
| 12015.500.31350 | 1270 | 50 | .0217 | 0.50 |

Technical data

Characteristic



- Paper jam-resistant Crease-resistant / self-healing
- Polyester-basis/ -carrier
- Repositionable

Compatibility

- For a hard substrate packing.
- For Plate Cylinder

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. These shall be beyond our control, and be subject to your exclusive responsibility. The sale of our products shall be subject to our current General Terms and Conditions.



FOLABASE H48

