

DATA SHEET 12000.100.99900

Folabase U

UNDERPACKING FOIL, NON ADHESIVE

Folabase U offers reliable support for adaptation to cylinder circumferences and print lengths in offset printing presses and ensures optimum dot transfer.

Folabase U can be applied very easy beneath printing formes and rubber blankets. Furthermore the material can be used in coating units in combination with our compressible Folacomp underpacking to achieve ideal rolling conditions.

Folabase U consists of a biaxial stretched polyester layer which offers high dimension stability. The thickness tolerance is low. The material composition has an extremely high swell resistance to dampening solutions and cleaning agents and shows fewer tendencies to breaks.

For product introduction by video please click [here](#).

Rolls

Art.Number	Nominal thickness (inch)	Nominal thickness (mm)
12000.040.11300	.0016	0.04
12000.080.11300	.0031	0.08
12000.100.11300	.0039	0.10
12000.120.11300	.0047	0.12
12000.140.11300	.0055	0.14
12000.160.11300	.0063	0.16
12000.180.11300	.0071	0.18
12000.200.11300	.0079	0.20
12000.230.11300	.0090	0.23
12000.250.11300	.0098	0.25
12000.280.11300	.011	0.28
12000.300.11300	.0118	0.30
12000.350.11300	.014	0.35

Technical data

Characteristic



- Paper jam-resistant Crease-resistant / self-healing
- Polyester-basis/ -carrier

Compatibility

- For Blanket Cylinder
- For a hard substrate packing.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. These shall be beyond our control, and be subject to your exclusive responsibility. The sale of our products shall be subject to our current General Terms and Conditions.

FOLABASE U

Polyesterfolie

